



YH-150V-C-2S

Large size high speed Vertical clamping/Vertical injection Plastic Molding Machine

**主要規格 Specifications**

射出系統 INJECTION UNIT			V	VR(圓盤)
螺桿直徑	Screw Diameter	mm	46	52
射料壓力	Injection Pressure	kgf/cm <sup>2</sup>	1667	1304
理論射出容積	Injection Capacity	cm <sup>3</sup>	316	403
最大射出重量	Injection Weight(P.S)	gr	284	363
		oz	10	13

射出率	Injection Rate	cc/s	109	139
螺桿回轉數	Screw Speed	r.p.m	0 ~ 150	
螺桿行程	Screw Stroke	mm	190	
噴嘴行程	Nozzle Stroke	mm	200	
噴嘴頂力	Nozzle Contact Force	tf	3.5	
<b>鎖模系統 CLAMPING UNIT</b>				
鎖模方式	Clamping System	--	Upper Mold Moving Direct Clamping Mechanism	
鎖模力	Clamping Force	tf	150	
鎖模行程	Clamping Stroke	mm	250	
最大空間	Max. Mould Space	mm	550	
最小模厚	Min. Mould Space	mm	300	
模板尺寸	Overall Size of Platens(HxV)	mm	920x690	
柱內尺寸	Space Between Columns(HxV)	mm	650x420	
油壓突針力	Hydraulic Ejector Force	tf	2.7	
突針行程	Ejector Stroke	mm	突出 50	
<b>圓盤系統 TABLE DIAMETER</b>				
圓盤直徑	Rotary Table Vnit	mm		1500
圓盤回轉角度	Table Rotation Angle	°		180度(反覆迴轉)
模具最大外型尺寸	Max. Mould Dimensions	mm		480x480
模具站數	Number of Molds	Sets		2
<b>電氣及其他 ELECTRICAL EQUIPMENT &amp; GENERAL</b>				
電動機	Drive Motor	kw	18.6(25HP)	
電熱	Heater	kw	10	



