



YHT-350

Images To follow

Main Standard :

INJECTION UNIT		
Screw Diameter	mm	Ø65
Injection Pressure	kgf/cm ²	1450
Injection Capacity	cm ³	862
Injection Weight(P.S)	gr	770
	oz	27
Injection Rate	cc/s	300
Screw Speed	r.p.m	0~150
Screw Stroke	mm	260
Nozzle Stroke	mm	550
Nozzle Contact Force	tf	8.0
CLAMPING UNIT		
Clamping System	--	Hydraulic
Clamping Force	tf	350
Clamping Stroke	mm	500
Max. Mould Space	mm	1000
Min. Mould Space	mm	500
Overall Size of Platens(HxV)	mm	1580 x 1580
Space Between Columns(HxV)	mm	1200 x 1200
Hydraulic Ejector Force	tf	8.0
Ejector Stroke	mm	150 (the lower plat eject 80)
ELECTRICAL EQUIPMENT & GENERAL		
Drive Motor	kw	44(60HP)
Heater	kw	24
Dimension of Machine(LxWxH)	m	5.75 x 2 x 4
Weight of Machine	t	17 / 6 / 1.29

Shipping Size(LxWxH)	m	5.8 x 2 x 1.85 2.3 x 2.2 x 1.7 3.1 x 1.25 x 1.45
Shipping Weight	t	17.4 / 6.13 / 1.42
Oil Tank Capacity	l	800
Cooling Water	l/hr	2000 ~ 2200

☐ Figures shown herein are subject to change without notice.

☐ Screw and clamping force can be design as customer's request.

